

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/09/2015

Reviewed on 06/09/2015

1 Identification

- **Product identifier**
- **Trade name:** Pure Metallic Basecoat & Effects Part A
- **Article number:** 400-BP-1500
- **Information department:** Product safety department
- **Emergency telephone number:** Chemtrec 800-424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS08 Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1B H350 May cause cancer.

Repr. 2 H361 Suspected of damaging fertility or the unborn child.



GHS07

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**
- **GHS label elements**
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS07 GHS08

- **Signal word** Danger

(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/09/2015

Reviewed on 06/09/2015

Trade name: Pure Metallic Basecoat & Effects Part A

(Contd. of page 1)

· **Hazard-determining components of labeling:**

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)
4-nonylphenol, branched
Stoddard solvent

· **Hazard statements**

Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.
May cause genetic defects.
May cause cancer.
Suspected of damaging fertility or the unborn child.

· **Precautionary statements**

Avoid breathing dust/fume/gas/mist/vapors/spray
Wear protective gloves.
Wear eye protection / face protection.
Wash thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
Specific treatment (see on this label).
Wash contaminated clothing before reuse.
If exposed or concerned: Get medical advice/attention.
If skin irritation or rash occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
If on skin: Wash with plenty of water.
Take off contaminated clothing and wash it before reuse.
Store locked up.
Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1
Fire = 1
Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = *1
Fire = 1
Reactivity = 0

(Contd. on page 3)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/09/2015

Reviewed on 06/09/2015

Trade name: Pure Metallic Basecoat & Effects Part A

(Contd. of page 2)

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

- **Dangerous components:**

25068-38-6	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight \leq 700)	74.43%
100-51-6	Benzyl alcohol	20.03%
84852-15-3	4-nonylphenol, branched	5.15%
8052-41-3	Stoddard solvent	0.1%

4 First-aid measures

- **Description of first aid measures**
- **General information:**
Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/09/2015

Reviewed on 06/09/2015

Trade name: Pure Metallic Basecoat & Effects Part A

(Contd. of page 3)

- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:**
 - Do not allow product to reach sewage system or any water course.
 - Inform respective authorities in case of seepage into water course or sewage system.
 - Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
 - Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 - Dispose contaminated material as waste according to item 13.
 - Ensure adequate ventilation.
- **Reference to other sections**
 - See Section 7 for information on safe handling.
 - See Section 8 for information on personal protection equipment.
 - See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
 - Ensure good ventilation/exhaustion at the workplace.
 - Open and handle receptacle with care.
 - Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
 - Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
 - **Requirements to be met by storerooms and receptacles:** No special requirements.
 - **Information about storage in one common storage facility:** Not required.
 - **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/09/2015

Reviewed on 06/09/2015

Trade name: Pure Metallic Basecoat & Effects Part A

(Contd. of page 4)

- **Control parameters**

· Components with limit values that require monitoring at the workplace:	
100-51-6 Benzyl alcohol	
WEEL	Long-term value: 10 ppm
8052-41-3 Stoddard solvent	
PEL	Long-term value: 2900 mg/m ³ , 500 ppm
REL	Long-term value: 350 mg/m ³ Ceiling limit value: 1800* mg/m ³ *15-min
TLV	Long-term value: 525 mg/m ³ , 100 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.

- **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/09/2015

Reviewed on 06/09/2015

Trade name: Pure Metallic Basecoat & Effects Part A

(Contd. of page 5)

· **Eye protection:**

Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**· **General Information**· **Appearance:**

Form:	Fluid
Color:	According to product specification
Odor:	Characteristic
Odour threshold:	Not determined.

· **pH-value:** Not determined.· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	205 °C (401 °F)

· **Flash point:** 101 °C (214 °F)· **Flammability (solid, gaseous):** Not applicable.· **Ignition temperature:** 435 °C (815 °F)· **Decomposition temperature:** Not determined.· **Auto igniting:** Product is not selfigniting.· **Danger of explosion:** Product does not present an explosion hazard.· **Explosion limits:**

Lower:	1.3 Vol %
Upper:	13.0 Vol %

· **Vapor pressure at 20 °C (68 °F):** 0.1 hPa· **Density at 20 °C (68 °F):** 1.121 g/cm³ (9.355 lbs/gal)· **Relative density** Not determined.· **Vapour density** Not determined.· **Evaporation rate** Not determined.· **Solubility in / Miscibility with**

Water:	Miscible
---------------	----------

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/09/2015

Reviewed on 06/09/2015

Trade name: Pure Metallic Basecoat & Effects Part A

(Contd. of page 6)

· Partition coefficient (n-octanol/water): Not determined.	
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	0.1 %
VOC content:	0.1 %
	1.1 g/l / 0.01 lb/gl
Solids content:	79.8 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

100-51-6 Benzyl alcohol

Oral	LD50	1230 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/09/2015

Reviewed on 06/09/2015

Trade name: Pure Metallic Basecoat & Effects Part A

(Contd. of page 7)

Harmful
Irritant
Carcinogenic.
The product can cause inheritable damage.

- **Carcinogenic categories**

· IARC (International Agency for Research on Cancer)
None of the ingredients is listed.
· NTP (National Toxicology Program)
None of the ingredients is listed.
· OSHA-Ca (Occupational Safety & Health Administration)
None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Ecotoxicological effects:**
- **Remark:** Toxic for fish
- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
Also poisonous for fish and plankton in water bodies.
Toxic for aquatic organisms
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/09/2015

Reviewed on 06/09/2015



Trade name: Pure Metallic Basecoat & Effects Part A

(Contd. of page 8)

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- | | |
|---|---|
| <ul style="list-style-type: none"> · UN-Number · DOT · IMDG, IATA | <p style="margin-left: 20px;">not regulated
UN3082</p> |
| <ul style="list-style-type: none"> · UN proper shipping name · DOT · IMDG
 · IATA | <p style="margin-left: 20px;">not regulated
ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
LIQUID, N.O.S. (reaction product: bisphenol-A-
(epichlorhydrin) epoxy resin (number average molecular
weight ≤ 700), 4-nonylphenol, branched), MARINE
POLLUTANT</p> <p style="margin-left: 20px;">ENVIRONMENTALLY HAZARDOUS SUBSTANCE,
LIQUID, N.O.S. (reaction product: bisphenol-A-
(epichlorhydrin) epoxy resin (number average molecular
weight ≤ 700), 4-nonylphenol, branched)</p> |
| <ul style="list-style-type: none"> · Transport hazard class(es) · DOT · Class | <p style="margin-left: 20px;">not regulated</p> |
| <ul style="list-style-type: none"> · IMDG, IATA <div style="display: flex; align-items: center; gap: 10px;">   </div> | <p style="margin-left: 20px;">9 Miscellaneous dangerous substances and articles
9</p> |
| <ul style="list-style-type: none"> · Class · Label | <p style="margin-left: 20px;">9 Miscellaneous dangerous substances and articles
9</p> |
| <ul style="list-style-type: none"> · Packing group · DOT | <p style="margin-left: 20px;">not regulated</p> |

(Contd. on page 10)

us

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/09/2015

Reviewed on 06/09/2015

Trade name: Pure Metallic Basecoat & Effects Part A

(Contd. of page 9)

· IMDG, IATA	III
· Environmental hazards:	Product contains environmentally hazardous substances: 4-nonylphenol, branched, reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)
· Marine pollutant:	Yes
· Special marking (IATA):	Symbol (fish and tree)
· Special precautions for user	Warning: Miscellaneous dangerous substances and articles
· Danger code (Kemler):	90
· EMS Number:	F-A,S-F
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· Transport/Additional information:	
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· UN "Model Regulation":	UN3082, Environmentally hazardous substances, liquid, n.o.s. (reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700), 4-nonylphenol, branched), 9, III

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

- **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

- **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

(Contd. on page 11)

Safety Data Sheet

acc. to OSHA HCS

Printing date 06/09/2015

Reviewed on 06/09/2015

Trade name: Pure Metallic Basecoat & Effects Part A

(Contd. of page 10)

- **Proposition 65**

· Chemicals known to cause cancer:
None of the ingredients is listed.
· Chemicals known to cause reproductive toxicity for females:
None of the ingredients is listed.
· Chemicals known to cause reproductive toxicity for males:
None of the ingredients is listed.
· Chemicals known to cause developmental toxicity:
None of the ingredients is listed.

- **Carcinogenic categories**

· EPA (Environmental Protection Agency)
None of the ingredients is listed.
· TLV (Threshold Limit Value established by ACGIH)
None of the ingredients is listed.
· NIOSH-Ca (National Institute for Occupational Safety and Health)
None of the ingredients is listed.

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS07 GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight ≤ 700)
4-nonylphenol, branched
Stoddard solvent

- **Hazard statements**

Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.
May cause genetic defects.
May cause cancer.
Suspected of damaging fertility or the unborn child.

- **Precautionary statements**

Avoid breathing dust/fume/gas/mist/vapors/spray

(Contd. on page 12)

US

Safety Data Sheet acc. to OSHA HCS

Printing date 06/09/2015

Reviewed on 06/09/2015

Trade name: Pure Metallic Basecoat & Effects Part A

(Contd. of page 11)

*Wear protective gloves.**Wear eye protection / face protection.**Wash thoroughly after handling.**Contaminated work clothing must not be allowed out of the workplace.**Obtain special instructions before use.**Do not handle until all safety precautions have been read and understood.**If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**Specific treatment (see on this label).**Wash contaminated clothing before reuse.**IF exposed or concerned: Get medical advice/attention.**If skin irritation or rash occurs: Get medical advice/attention.**If eye irritation persists: Get medical advice/attention.**If on skin: Wash with plenty of water.**Take off contaminated clothing and wash it before reuse.**Store locked up.**Dispose of contents/container in accordance with local/regional/national/international regulations.***· National regulations:****· Information about limitation of use:***Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.***· Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

*This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.***· Department issuing SDS:** Environment protection department.**· Contact:** Mr. Williams**· Date of preparation / last revision** 06/09/2015 / -**· Abbreviations and acronyms:***ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)**IMDG: International Maritime Code for Dangerous Goods**DOT: US Department of Transportation**IATA: International Air Transport Association**ACGIH: American Conference of Governmental Industrial Hygienists**EINECS: European Inventory of Existing Commercial Chemical Substances**ELINCS: European List of Notified Chemical Substances**CAS: Chemical Abstracts Service (division of the American Chemical Society)**NFPA: National Fire Protection Association (USA)**HMIS: Hazardous Materials Identification System (USA)**VOC: Volatile Organic Compounds (USA, EU)**LC50: Lethal concentration, 50 percent*

(Contd. on page 13)

us

Safety Data Sheet
acc. to OSHA HCS

Printing date 06/09/2015

Reviewed on 06/09/2015

Trade name: Pure Metallic Basecoat & Effects Part A

(Contd. of page 12)

LD50: Lethal dose, 50 percent
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
Muta. 1B: Germ cell mutagenicity, Hazard Category 1B
Carc. 1B: Carcinogenicity, Hazard Category 1B
Repr. 2: Reproductive toxicity, Hazard Category 2

US